



DESIGN REPORT OF SAFETY DATA SHEET

No.: 250100320448581E

Date: May.6,2025



Name of the sample	Cylindrical Lithium-ion Rechargeable Cell HYLN IMR18650-1800mAh		
Applicant	Henan Hengyi Lithium Energy Technology Co.,Ltd.		
Supplier	Henan Hengyi Lithium Energy Technology Co.,Ltd.		
Composition of the sample	Lithium manganate: 30%~34%; Acetylene black; Graphite: 13%~18%; Lithium hexafluorophosphate: 13%~18%; Copper: 4%~6%; Aluminium: 2%~4%; Polypropylene: 0.3%~0.5%; Steel Shell: 20%~25%		
Warranty of Design	GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS) Tenth revised edition		
Design Result of SDS please see next page.			
Designer	孙越越	Approver	For and on behalf of CCIC JIANGSU CO., LTD. 中国检验认证集团江苏有限公司 华越

4

授权签字人 Authorized Signature(s)

Notes: This SDS is valid before the implementation of the Eleventh revised edition GHS.

Test is Located on: CCIC Dangerous Goods Identification Center (47 Qingyang North Road, Tianning District, Changzhou, China)
Tel: +86-519-83277160

Cylindrical Lithium-ion Rechargeable
Cell HYLN IMR18650-1800mAh
Warranty of Design: GHS (Tenth Revised
Edition)


SAFETY DATA SHEET

SDS

No.: 250100320448581E

Date: May 6, 2025

Version: 1.1



Section 1 Product and Company Identification

> Product Identifier

Product Name Cylindrical Lithium-ion Rechargeable Cell HYLN IMR18650-1800mAh

> Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Relevant Identified Uses Please consult manufacturer.

Uses Advised Against Please consult manufacturer.

> Details of the Supplier of the Safety Data Sheet

Applicant Name Henan Hengyi Lithium Energy Technology Co.,Ltd.
Application Address Building 3, Xinhua Industrial Park, Longmen Avenue, Xinhua District, Pingdingshan City, Henan, P.R.China
Applicant Post Code 467000
Applicant Telephone +86-18037581522
Applicant Fax —
Applicant E-mail hypz002@hylnkj.cn
Supplier Name Henan Hengyi Lithium Energy Technology Co.,Ltd.
Supplier Address Building 3, Xinhua Industrial Park, Longmen Avenue, Xinhua District, Pingdingshan City, Henan, P.R.China
Supplier Post Code 467000
Supplier Telephone +86-18037581522
Supplier Fax —
Supplier E-mail hypz002@hylnkj.cn

> Emergency Phone Number

Emergency Phone Number +86-13525376185

Section 2 Hazards Identification

Hazard class and label elements of the product according to GHS (the tenth revised edition):

> GHS Hazard Class

This product meets the definition of an article. Under the Globally Harmonized System of Classification and Labeling of Chemicals (GHS), "Articles" as defined in the Hazard Communication Standard (29 CFR 1910.1200) of the Occupational Safety and Health Administration of the United States of America, or by similar definition, are outside the scope of the system. [Rev.10 (2023) Part 1.3.2.1.1]

> GHS Label Elements

Cylindrical Lithium-ion Rechargeable
Cell HYLN IMR18650-1800mAh
Warranty of Design: GHS (Tenth Revised
Edition)

SAFETY DATA SHEET

SDS

No.: 250100320448581E
Date: May.6,2025
Version: 1.1

Pictogram Not applicable

Signal Word **Not applicable**

> Hazard Statements

Not applicable

> Precautionary Statements

Prevention

Do not open or disassemble.
Do not expose to high temperatures or open fire.
Do not mix with batteries of varying sizes, chemistries or types.
Avoid using external impact battery.

Response

Not applicable

Storage

Store under roof in cool, dry, well-ventilated areas.

Disposal

Dispose of contents/container in accordance with local/regional/national/ international regulations.

Section 3 Composition/Information on Ingredients

Component	CAS No.	EC No.	Concentration (weight percent, %)
Lithium manganate	12057-17-9	-	30~34
Acetylene black	1333-86-4	215-609-9	Commercial secrets
Graphite	7782-42-5	231-955-3	13~18
Lithium hexafluorophosphate	21324-40-3	244-334-7	13~18
Copper	7440-50-8	231-159-6	4~6
Aluminium	7429-90-5	231-072-3	2~4
Polypropylene	9003-07-0	-	0.3~0.5
Steel Shell	-	-	20~25

Section 4 First Aid Measures

> Description of First Aid Measures

General Advice

Immediate medical attention is required. Show this safety data sheet (SDS) to the doctor in attendance.

Eye Contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician if

Cylindrical Lithium-ion Rechargeable
Cell HYLN IMR18650-1800mAh
Warranty of Design: GHS (Tenth Revised
Edition)

SAFETY DATA SHEET

SDS

No.: 250100320448581E
Date: May.6,2025
Version: 1.1

	feel uncomfortable.
Skin Contact	Take off contaminated clothing and shoes immediately. Wash off with plenty of water for at least 15 minutes and consult a physician if feel uncomfortable.
Ingestion	Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.
Inhalation	Move victim into fresh air. If breathing is difficult, give oxygen. Do not use mouth to mouth resuscitation if victim ingested or inhaled the substance. If not breathing, give artificial respiration and consult a physician immediately.
Protecting of First-aiders	Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.

> Most Important Symptoms and Effects, both Acute and Delayed

- 1 Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

> Indication of Any Immediate Medical Attention and Special Treatment Needed

- 1 Treat symptomatically.
- 2 Symptoms may be delayed.

Section 5 Fire Fighting Measures

> Extinguishing Media

Suitable Extinguishing Media	Use water spray to extinguish fire. Cool surrounding Lithium batteries with water spray.
Unsuitable Extinguishing Media	Do not use a solid water stream as it may scatter or spread fire.

> Specific Hazards Arising from the Substance or Mixture

- 1 Containers may explode when heated.
- 2 Fire exposed containers may vent contents through pressure relief valves.
- 3 May expansion or decompose explosively when heated or involved in fire.

> Advice for Firefighters

- 1 As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear.
- 2 Fight fire from a safe distance, with adequate cover.
- 3 Prevent fire extinguishing water from contaminating surface water or the ground water system.

Section 6 Accidental Release Measure

> Personal Precautions, Protective Equipment and Emergency Procedures

- 1 Ensure adequate ventilation. Remove all sources of ignition.
- 2 Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.
- 3 Use personal protective equipment. Avoid breathing vapours, mist, gas or dust.

> Environmental Precautions



Cylindrical Lithium-ion Rechargeable
Cell HYLN IMR18650-1800mAh
Warranty of Design: GHS (Tenth Revised
Edition)

SAFETY DATA SHEET

SDS

No.: 250100320448581E
Date: May.6,2025
Version: 1.1

- 1 Prevent further leakage or spillage if safe to do so.
- 2 Discharge into the environment must be avoided.

> Methods and Materials for Containment and Cleaning Up

- 1 Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
- 2 Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations.
- 3 Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Section 7 Handling and Storage

> Precautions for Handling

- 1 Handling is performed in a well ventilated place.
- 2 Wear suitable protective equipment.
- 3 Avoid contact with skin and eyes.
- 4 Keep away from heat/sparks/open flames/ hot surfaces.
- 5 Take precautionary measures against static discharges.

> Precautions for Storage

- 1 Keep containers tightly closed.
- 2 Keep containers in a dry, cool and well-ventilated place.
- 3 Keep away from heat/sparks/open flames/ hot surfaces.
- 4 Store away from incompatible materials and foodstuff containers.

Section 8 Exposure Controls/Personal Protection

> Control Parameters

Occupational Exposure Limit Values

Component	Country/Region	Limit Value - Eight Hours		Limit Value - Short Term	
		ppm	mg/m ³	ppm	mg/m ³
Acetylene black 1333-86-4	USA - OSHA	-	3.5	-	-
	South Korea	-	3.5	-	-
	Ireland	-	3.5	-	7
	France	-	3.5	-	-
	Denmark	-	3.5	-	7
	Australia	-	3	-	-
Graphite 7782-42-5	USA - OSHA	-	15	-	-
	South Korea	-	2	-	-
	Ireland	-	10	-	-

Cylindrical Lithium-ion Rechargeable
Cell HYLN IMR18650-1800mAh

Warranty of Design: GHS (Tenth Revised
Edition)

SAFETY DATA SHEET

SDS

No.: 250100320448581E

Date: May.6,2025

Version: 1.1

	Germany (DFG)	-	4	-	-
	Denmark	-	2.5	-	5
	Australia	-	3 (4)	-	-
Copper 7440-50-8	The Netherlands	-	0.1	-	-
	Poland	-	0.2	-	-
	Latvia	-	0.5	-	1
	Germany (DFG)	-	0.01	-	0.02
Aluminium 7429-90-5	USA - OSHA	-	15	-	-
	South Korea	-	10	-	-
	Ireland	-	1	-	-
	Germany (DFG)	-	4	-	-
	Denmark	-	5	-	10
	Australia	-	10	-	-

Biological Limit Values

Component	Source	Biological monitoring index	Biological limits value	Sampling time	Remark
Lithium hexafluorophosphate	SCOEL(EU)	Fluorine/urine	8mg/L 检验检测专用章 3204	end of shift	

Monitoring Methods

- 1 EN 14042 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.
- 2 GBZ/T 160 Determination of toxic substances in workplace air(Series effective standard)and GBZ/T 300 Determination of toxic substances in workplace air(Series standard).

> Engineering Controls

- 1 Ensure adequate ventilation, especially in confined areas.
- 2 Ensure that eyewash stations and safety showers are close to the workstation location.
- 3 Use explosion-proof electrical/ventilating/lighting/equipment.
- 4 Set up emergency exit and necessary risk-elimination area.

> Personal Protection Equipment

Eye Protection	Tightly fitting safety goggles (approved by EN 166(EU) or NIOSH (US).
Hand Protection	Wear protective gloves (such as butyl rubber) , passing the tests according to EN 374(EU),US F739 or AS/NZS 2161.1 standard.
Respiratory protection	If exposure limits are exceeded or if irritation or other symptoms are experienced, use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges.
Skin and Body Protection	Wear fire/flame resistant/retardant clothing and antistatic boots.

Section 9 Physical and Chemical Properties

Appearance: Lithium ion battery cells, individually

Odor: No information available

Cylindrical Lithium-ion Rechargeable
Cell HYLN IMR18650-1800mAh
Warranty of Design: GHS (Tenth Revised
Edition)

SAFETY DATA SHEET

SDS

No.: 250100320448581E
Date: May.6,2025
Version: 1.1

packaged. Battery parameters:3.7V 1.8Ah 6.66Wh

Odor Threshold: No information available
Melting Point/Freezing Point (°C): No information available
Flash Point (°C)(Closed Cup): Not applicable
Flammability: No information available
Vapor Pressure (KPa): Not applicable
Relative Density(Water=1): No information available
n-Octanol/Water Partition Coefficient: No information available
Decomposition Temperature (°C): No information available
Particle characteristics: No information available

pH: No information available
Initial Boiling Point and Boiling Range (°C): No information available
Evaporation Rate: Not applicable
Upper/lower explosive limits[% (v/v)]: Upper limit: No information available; Lower limit: No information available
Relative Vapour Density(Air=1): Not applicable
Solubility: No information available
Auto-Ignition Temperature(°C): No information available
Kinematic Viscosity (mm²/s): Not applicable
Critical Temperature(°C): Not applicable

Section 10 Stability and Reactivity

Reactivity Contact with incompatible substances can cause decomposition or other chemical reactions.

Chemical Stability Stable under proper operation and storage conditions.

Possibility of Hazardous Reactions Mixtures with metallic acetylene, when heated, cause a fire or incandescence. Reacts severely with halogens, interhalogens or other strong oxidants, or causes a fire. Ultrafine powder will self-ignite in the air at room temperature.

Conditions to Avoid Incompatible materials, heat, flame and spark.

Incompatible Materials Metal acetylide, halogen, interhalogen, halogen oxides, nitric acid, nitrous oxide, nitrates, nitrites, halogen oxyacid salts, chromates, permanganates, inorganic peroxides, metal oxides and peroxyformic acid. Halogen, interhalogen, strong oxidant, water and acids. Oxidants, halogen, interhalogen and mercury.

Hazardous Decomposition products Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11 Toxicological Information

> Acute Toxicity

Component	CAS No.	LD ₅₀ (Oral)	LD ₅₀ (Dermal)	LC ₅₀ (Inhalation, 4h)
Acetylene black	1333-86-4	> 15400mg/kg(Rat)	> 3000mg/kg(Rabbit)	No information available
Lithium hexafluorophosphate	21324-40-3	50~300mg/kg(Rat)	275mg/kg(Rat)	No information available

> Skin Corrosion/Irritation

Cylindrical Lithium-ion Rechargeable
Cell HYLN IMR18650-1800mAh
Warranty of Design: GHS (Tenth Revised
Edition)

SAFETY DATA SHEET

SDS

No.: 250100320448581E
Date: May.6,2025
Version: 1.1

No information available

> Serious Eye Damage/Irritation

No information available

> Skin Sensitization

No information available

> Respiratory Sensitization

No information available

> Germ Cell Mutagenicity

No information available

> Carcinogenicity

ID	CAS No.	Component	IARC	NTP
1	12057-17-9	Lithium manganate	Not Listed	Not Listed
2	1333-86-4	Acetylene black	Category 2B	Not Listed
3	7782-42-5	Graphite	Not Listed	Not Listed
4	21324-40-3	Lithium hexafluorophosphate	Not Listed	Not Listed
5	7440-50-8	Copper	Not Listed	Not Listed
6	7429-90-5	Aluminium	Not Listed	Not Listed
7	9003-07-0	Polypropylene	Category 3	Not Listed
8	-	Steel Shell	Not Listed	Not Listed

> Reproductive Toxicity

No information available

> Reproductive Toxicity (Additional)

No information available

> STOT-Single Exposure

No information available

> STOT-Repeated Exposure

No information available

> Aspiration Hazard

No information available

Cylindrical Lithium-ion Rechargeable
Cell HYLN IMR18650-1800mAh
Warranty of Design: GHS (Tenth Revised
Edition)

SAFETY DATA SHEET

SDS

No.: 250100320448581E
Date: May.6,2025
Version: 1.1

Section 12 Ecological Information

> Acute Aquatic Toxicity

Component	CAS No.	Fish	Crustaceans	Algae
Copper	7440-50-8	LC ₅₀ : 0.665mg/L (96h)(Fish)	EC ₅₀ : 0.02mg/L (48h)	ErC ₅₀ : 7.9mg/L (96h)
Aluminium	7429-90-5	LC ₅₀ : 1.55mg/L (96h)(Fish)	No information available	No information available

> Chronic Aquatic Toxicity

No information available

> Others

**Persistence and
Degradability
Bioaccumulative
Potential
Mobility in Soil**

No information available

No information available

No information available

**Results of PBT and
vPvB Assessment**

Lithium manganate does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.

Acetylene black does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.

Graphite does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.

Lithium hexafluorophosphate does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.

Copper does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.

Aluminium does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.

Polypropylene does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.

Section 13 Disposal Considerations

**Waste Chemicals
Contaminated
Packaging
Disposal
Recommendations**

Before disposal should refer to the relevant national and local laws and regulation. Containers may still present chemical hazard when empty. Keep away from hot and ignition source of fire. Return to supplier for recycling if possible. Refer to Waste chemicals and Contaminated packaging.

Section 14 Transport Information

Cylindrical Lithium-ion Rechargeable
Cell HYLN IMR18650-1800mAh
Warranty of Design: GHS (Tenth Revised
Edition)

SAFETY DATA SHEET

SDS

No.: 250100320448581E
Date: May.6,2025
Version: 1.1

Transporting Label



Marine pollutant No

UN Number 3480

UN Proper Shipping Name LITHIUM ION BATTERIES(including lithium ion polymer batteries)

Transport Hazard Class 9

Transport Subsidiary Hazard Class NONE

Packing Group Packagings shall conform to the packing group II performance level

Report remarks According to United Nations Recommendations on the Transports of Dangerous Goods•Model Regulations, Lithium batteries(group) could be transported in accordance with the classification conclusions of this report when meet the requirements of UN38.3 test.

Section 15 Regulatory Information

> International Chemical Inventory

Component	EINECS	TSCA	DSL	IECSC	NZIoC	PICCS	KECL	AIIC	ENCS
Lithium manganate	×	√	×	√	√	×	√	×	×
Acetylene black	√	√	√	√	√	√	√	√	×
Graphite	√	√	√	√	√	√	√	√	×
Lithium hexafluorophosphate	√	√	×	√	×	√	√	√	×
Copper	√	√	√	√	√	√	√	√	×
Aluminium	√	√	√	√	√	√	√	√	×
Polypropylene	×	√	√	√	√	√	√	√	√
Steel Shell	×	×	×	×	×	×	×	×	×

【EINECS】 European Inventory of Existing Commercial Chemical Substances.

【TSCA】 United States Toxic Substances Control Act Inventory.

【DSL】 Canadian Domestic Substances List.

【IECSC】 China Inventory of Existing Chemical Substances.

【NZIoC】 New Zealand Inventory of Chemicals.

【PICCS】 Philippines Inventory of Chemicals and Chemical Substances.

【KECL】 Korea Existing Chemicals List.

【AIIC】 Australian Inventory of Industrial Chemicals.

【ENCS】 Japan List of Existing and New Chemical Substances.

Note

“√” Indicates that the substance included in the regulations

“×” That no data or included in the regulations

Cylindrical Lithium-ion Rechargeable
Cell HYLN IMR18650-1800mAh
Warranty of Design: GHS (Tenth Revised
Edition)

SAFETY DATA SHEET

No.: 250100320448581E

Date: May 6, 2025

SDS

Version: 1.1

Section 16 Additional Information

Creation Date May.6,2025
Revision Date May.6,2025
Reason for Revision -



> Disclaimer

This Safety Data Sheet (SDS) was prepared according to UN GHS (the 10th revised edition). The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.



Terms of the Using of the Report

1. The report is issued by CCIC according to the information of the chemicals and the information of its shipping provided by the applicant (shipper or his agent).
2. According to the demand of this SDS, CCIC requires the applicant to provide true and exact sample and data.
3. Information from applicant is the key of this SDS, so CCIC will not respond for the wrong of applicant.
4. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested.
5. This report will be effective only after it is signed by the inspector, approver and stamped by CCIC.
6. CCIC guarantees the objectivity and fairness of this report, and carries out confidentiality obligations on business secrets such as business information, technical documents and so on.
7. The partly duplicating of this report is prohibited without the written approver of CCIC.
8. The report is invalid when anything of the following happens-illegal transfer, embezzlement, imposture, modification or tampering in any media form.
9. The authenticity of the certificate can be checked by scan the security code of this certificate.

Notes : Test is Located on : CCIC Dangerous Goods Identification Center (47 Qingyang North Road, Tianning District, Changzhou, China)

Tel : +86-519-83277160

